




HB3

1200 × 1000 × 790 mm / 620 l



Art.-Nr.: 83421800

Technical data

Dimensions L x W x H (mm)	1200 x 1000 x 790		
Nesting height	0 mm		
Weight (kg)	44.0		
Volume (l)	l		
Material	PE		
Load capacity (kg)	 Stacking Load 5000 kg	 Holding Capacity 900 kg	 Dynamic Load 1900 kg

Characteristics

Colour: light grey
Runners: 3, welded
Stackable
Temperature stability: -30 °C to +40 °C, briefly up to +90 °C
Resistant to most chemicals and cleaning agents
Food-safe. HACCP compliant
Container is based on DIN EN 13626 and DIN EN ISO 12048

Options


Reinforcement profiles
Lid
Drain port

Loading quantities (Pcs / Approximate amount)

 Container	Container 20': – Container 40': –	Container 40' High Cube: – Conventional trailer 45' high cube container: 104
 Truck	MEGA-Trailer: 104	Jumbo: 112-120

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.

*3 **Stacking Load:** With a maximum stacking height of 6 boxes (5 on 1 stacking) and evenly distributed load at approx. 20 °C.
Dynamic Load: On a forklift with an evenly distributed load at a room temperature of approx. 20 °C.